AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A method of decomposing an image

comprising:

decomposing the image into a plurality of stripes, wherein at least one

stripe of the plurality of stripes spans opposing edges of the spanning said

image;

determining a layer base color, a layer size and a layer offset of at least

one stripe of the plurality of stripes;

separating the stripe into a foreground layer, a background layer and a

mask layer based on the layer base color and the layer offset; and

interpolating irrelevant pixel values in the foreground layer and

background layer for coder efficiency.

2. (Previously Presented) The method of claim 1 further comprising:

encoding the foreground layer, background layer, and mask layer.

3. (Previously Presented) The method of claim 2 wherein the

foreground layer and background layer are JPEG encoded, wherein the mask

layer is JBIG encoded.

4. (Previously Presented) The method of claim 1 wherein said

interpolating irrelevant pixel values further comprises:

Serial No.: 10/036,979

10/030,373

- 2 -

Examiner: Larose, Colin M.

Art Unit: 2623

10006292-1/JPW/MJB

determining the layer base color and the layer offset to a common reduced

area of at least one layer to identify image and mask layer values for all regions

except an overlapped common reduced area; and

separating the overlapped common reduced area into a foreground layer

and a background layer.

5. (Previously Presented) The method of claim 1 wherein said

interpolating irrelevant pixel values further comprises:

classifying at least one pixel within a selected block of a selected layer as

relevant or irrelevant;

generating a coefficient block representing a forward transform of the

selected block; and

modifying coefficient values to generate a modified coefficient block

subject to a set of pre-determined constraints including a constraint that the

relevant pixels have a same value in an inverse transformation of the modified

coefficient block as in the selected block.

(Previously Presented) The method of claim 5 wherein said 6.

modifying coefficient values includes:

selecting a coefficient from the coefficient block in a reverse zig-zag order

wherein the selected coefficient has a non-zero value; and

finding a feasible solution resulting in a zero quantizable selected

coefficient subject to the pre-determined constraints.

Serial No.: 10/036,979

- 3 -

Examiner: Larose, Colin M.

Art Unit: 2623

10006292-1/JPW/MJB

7. (Original) The method of claim 5 wherein the coefficient values are

modified subject to a constraint that no zero quantizable coefficient preceding the

selected coefficient in the reverse zig-zag order is permitted to become non-zero

quantizable.

8. (Original) The method of claim 5 wherein values of individual

elements of a mask classify pixels in corresponding positions within the selected

block as relevant or irrelevant.

9. (Previously Presented) The method of claim 5 further comprising:

providing the modified coefficient block to a block compression process.

10. (Previously Presented) The method of claim 5 wherein said

interpolating irrelevant pixel values further comprises applying a linear program

to identify a feasible solution resulting in a zero-quantizable coefficient subject to

the constraints.

11. (Previously Presented) The method of claim 10 further comprising

applying a quadratic program to generate a modified selected block having

-4-

minimal energy.

Serial No.: 10/036,979

10006292-1/JPW/MJB

Examiner: Larose, Colin M.

Art Unit: 2623

12. (Previously Presented) The method of claim 10 further comprising

terminating further modifications to the coefficient block if a ratio of the energy of

the modified block to the energy of the initial selected block exceeds a pre-

determined threshold.

13. (Original) The method of claim 5 wherein the forward transform is

one of a discrete cosine, a discrete sine, and a discrete Fourier transform.

14. (Previously Presented) A method of decomposing an image

comprising:

decomposing the image into a plurality of stripes;

decomposing at least one stripe into foreground and background image

layers, and a mask layer;

identifying an area of intersection of a common reduced foreground area

and a common reduced background areas, wherein the identifying further

comprises:

computing a maximum block range for a selected block of the area

of intersection; and

assigning at least one pixel within the selected block to one of the

foreground and background planes in accordance with whether the

average luminance of the selected block is closer to a previous average

foreground luminance or previous average background luminance,

Serial No.: 10/036,979

10006292-1/JPW/MJB

Examiner: Larose, Colin M.

Art Unit: 2623

- 5 -

respectively, if the maximum block range is not greater than a pre-

determined threshold; and

interpolating any irrelevant pixel values within the area of intersection for

coder efficiency for at least one layer.

(Original) The method of claim 14, wherein the area of intersection 15.

is selected to have an edge that is 8N pixels from at least one of an edge of the

common reduced foreground area and the common reduced background area,

wherein N is an integer, wherein N≥0.

(Previously Presented) The method of claim 14, wherein said 16.

interpolating any irrelevant pixel values further comprises:

selecting a block of pixels; and

classifying at least one pixel with the selected block as irrelevant or

relevant.

(Previously Presented) The method of claim 16, wherein said 17.

interpolating any irrelevant pixel values further comprises:

calculating an average value of at least one relevant pixel within the

selected block; and

assigning the average value to at least one irrelevant pixels within the

selected block.

Serial No.: 10/036,979

10006292-1/JPW/MJB

Examiner: Larose, Colin M.

- 6 -

Art Unit: 2623

18. (Previously Presented) The method of claim 14, wherein said

identifying an area of intersection further comprises:

computing a maximum block range for a selected block of the area of

intersection;

dividing pixels within the selected block into a plurality of groups; and

assigning at least one selected group to one of the foreground and

background planes in accordance with a relative average luminance value of the

selected group and another group, if the maximum block range exceeds a pre-

determined threshold.

19. (Previously Presented) The method of claim 18, wherein said

assigning at least one selected group further comprises assigning the selected

group to the background layer and the other group to the foreground layer if an

average luminance of the selected group is greater than an average luminance of

the other group, wherein the selected group is assigned to the foreground layer

and the other group to the background layer if the average luminance of the

selected group is not greater than the average luminance of the other group.

20. (Cancelled)

Serial No.: 10/036,979

10006292-1/JPW/MJB

Examiner: Larose, Colin M. Art Unit: 2623

-7-